

ECO 486

HIGHLY TECHNOLOGICAL CLOSE ENCOUNTER

THE GENERAL PURPOSE
PORTABLE TERMINAL
WITH INTEGRATED LASER
BAR CODE READER
BASED ON STANDARD PC
TECHNOLOGY.

DOS OPERATING SYSTEM,
THE DEVICE HAS A 32 BIT
486 PROCESSOR AND A
MEMORY CAPACITY OF
2 MB RAM AND UP TO
4 MB FLASH.



METEOR

ECO 486

portable terminal
terminale portatile

The general purpose portable terminal with integrated laser bar code reader is based on standard PC technology.
The device has a 32 bit 486 processor and a memory capacity of 2 Mb RAM and up to 4 Mb Flash.
It weighs 235 g., batteries included.

Specifications

Microprocessor	• 486 - 32 bit
Microprocessore	• 486 - 32 bit
Standard memory	• RAM: 2 MB - Flash: 2 or 4 MB
Memoria standard	• RAM: 2 MB - Flash: 2 or 4 MB
Operating system	• ROM-DOS (c)
Sistema operativo	• ROM-DOS (c)
Programming	• C (BORLAND) Language
Programmazione	• C (BORLAND)
Battery control	• internal battery charger and four levels battery monitor
Controllo batterie	• carica batteria interno, 4 livelli controllo carica
Bar Codes	• Code 39, Code 128, Code 93, EAN-UPC with add-on,
Codice a barre	• Codabar Interleaved 2/5, 2/5 industrial, 2/5 Standard, Matrix 2/5
Display	• high contrast Supertwist 97x32 graphic, LCD panel
Real-Time Clock and calendar	
Interface	• RS232
Keyboard	• 24 keys
Tastiera	• 24 tasti
Laser class	• CDRH Class II device
Power	• 4 AAA size NiMH 600 mAH rechargable batteries (supplied)
Alimentazione	• 4 batterie ricaricabili NiMH 600 mAH (incluse)
Buzzer	• piezoelectric buzzer
Dimensions	• 6.6in. Height; 2.3in. Width; 1.3in. Depth
Dimensioni	• 16,8 cm. altezza; 5,9 cm. larghezza; 3,9 cm. spessore
Weight	• 235 gms
Peso	• 235 grammi
ESD	• protection 15kv immunity to electrostatic discharges
	• protezione fino a 15 kv per scariche elettrostatiche
Drop	• It works normally allowed drops till 3,0 ft to concrete
Caduta	• funzioni normali dopo caduta da 1 metro su cemento
Humidity	• 95% relative humidity (without condensation)
Umidità	• 95% umidità relativa (senza condensa)
Temperature	• operational: from 0° to 45 °C - stock: from 0° to 50 °C
Temperatura	• operativa: da 0° a 45 °C - magazzino: da 0° a 50 °C
Enclosure protection	• to IP53
Protezione involucro	• fino a IP53
Accessories	• pc cable and power supply (supplied)
Accessori	• cavo pc ed alimentatore (incluso)

METEOR

Factory: ITALY-VENICE-SPINEA - Via delle Macchine, 24
E-mail: meteor@meteorbarcode.it
Website: www.meteorbarcode.it
Tel. +39 041 5412600 - Fax +39 041 5412231